



# No Hydro Damp-Proofing Cream

## Product Description

No Hydro Damp-Proofing Cream is for remedial rising damp treatments. It is a cream that is injected into holes drilled along a mortar bed using a special applicator gun. Once installed, the double-strength formulation spreads along the mortar bed before curing to form a damp-proof course.

## Benefits

- Easy to install – no costly and complicated electric pumps required
- Usable in a wide variety of walls including brick, stone and rubble construction

## Properties

Appearance	Thick, white cream	
Coverage per 10 m of wall <sup>(1)</sup>	115 mm thick wall	1 litre
	230 mm thick wall	2 litre
	345 mm thick wall	3 litre
	450 mm thick wall	4 litre
Storage	Store flat and in a cool, dry, well ventilated place. Keep container closed	
Shelf Life	12 months in unopened pack	

## Application Information

### Preparation

Set your SDS drill to rotary hammer and select a 12 mm drill bit in excess of the required drill depth. Depending on the thickness of the wall, mark the drill bit the following distances from the tip:

Depth of Drill Hole	Wall Thickness			
	4½" (115 mm)	9" (230 mm)	13½" (345 mm)	18" (460 mm)
	95 mm	210 mm	325 mm	440 mm

### Application

When treating from outside a row of holes should be drilled into the mortar course 120 mm apart and approximately 150 mm above the ground. When treating from the inside the holes should be drilled into the lowest accessible mortar course. Drill the holes the necessary depth ensuring you reduce your drilling pressure once you reach 40 mm short of the full hole depth. Reducing pressure ensures a cleaner hole and prevents damage to the far side of the wall.



Insert the product into the applicator gun, ensuring the pressure piston is fully extended.

Fully insert the nozzle into the first drilled hole, and then inject No Hydro Damp-Proofing Cream while withdrawing the nozzle at a steady rate. Stop injecting just before removing the nozzle from the wall. Repeat for remaining holes.

*The information supplied is in good faith and is based on expertise, experience & usage, however all recommendations are offered without warranty or guarantee, since the usage circumstances are beyond our control. All goods are sold in accordance with Toner Dampproofing Supplies Ltd Conditions of Sale, copies of which are available on request. Customers are advised that products, techniques and / or codes of practice are under constant review and changes occur without notice. You can always download updated information of products, techniques and / or codes of practice at [www.nohydro.co.uk](http://www.nohydro.co.uk)*

